



Ladder external width 490mm

**6047112**

GTIN: 4007126010803

Application as fixed vertical ladders for buildings and machinery, suitable for indoor and outdoor use.

**Material**

Aluminium, uncoated + Steel, galvanised

Length in m | Number of rungs

3,08 m | 11 Rungs

- Single-flight according to the basic requirements of DIN 18799
- Resistant to corrosion in neutral and slightly acidic environments
- Sturdy, easy-grip rail profiles
- Extendable using ladder connectors
- Easy to install
- Straight mounting surface required
- Fall arresting system / safety cage required: for fixed ladders on buildings and on machinery from a climbing height of 3000 mm

Scope of delivery:

Ladder sections, ladder connectors, ladder caps, wall brackets 185 mm,





exit rail (AHB-K), exit extension, safety cage rail, rear safety cage vertical bars, bar connectors, caps, max. length for shipment 4200 mm, multi-section over 4200 mm

- Ladder sections can be shortened without risk of corrosion
- Non-slip rungs with crosswise and lengthwise profiling

Specifications

Ladder external width in mm	490
Rung spacing 280mm	✓
Material	Aluminium, uncoated + Steel, galvanised
Length in m	3,08
safety cage basket Length in m	1,96
Number of rungs	11
Weight (KG)	40,0
Rail dimension	Square profile 72x25mm
Rung dimension	30x30mm
Length in m   Number of rungs	3,08 m   11 Rungs
Width in mm	440

