

Shaft cover HS8

9552002

GTIN: 4007126006790

Shaft cover flush to the ground, suitable for cars (EN 124 class B) or trucks (EN 124 class D), approved for flowing urban traffic. Safe operation with gas pressured springs as opening aid and self-engaging cover. Lid with integrated seal. Locked by closure with brass nut for male triangular wrench. Prepared for locking with safety lock. Deeper locking covered by three-sided brass bolt. Other sizes, versions and materials on request.

Width in mm
1200x1200 mm

Load class
D 400kN - EN124

- rectangular design
- Surface water proof
- safe to drive on
- odour proof
- for installation at ground level
- stainless steel 1.4301/ASTM 304

options on request:

- square and multi-part design
- material 1.4571 / ASTM 316Ti or galvanized steel
- emergency unlocking to allow the cover to be opened from below
- internal railing
- safety guard rail in various versions
- backpressure/flood proof up to 0.2 bar
- Bracket for potential equalisation



Copyright © 2026 Hailo. Alle Rechte vorbehalten.

- Cover with 50 mm tray for on-site filling with paving, concrete or asphalt
- electric or hydraulic opening
- Insulation to reduce condensation

Note: Not all optional equipment can be freely combined.



Specifications

Material	Stainless steel 1.4301 / AISI 304
Thightness	surface water proof and odour proof
flush with ground	✔
rectangular	✔
suitable for moving traffic	✔
Load class	D 400kN - EN124
Width in mm	1200x1200 mm

Copyright © 2026 Hailo. Alle Rechte vorbehalten.