



Ladder external width 490mm

9647112

GTIN: 4007126011428

Application as fixed vertical ladders for buildings and machinery, suitable for indoor and outdoor use.

Material


Steel 1.0037 / ASTM A36, galvanised

Length in m | Number of rungs

3,08 m | 11 Rungs



- Single-flight according to the basic requirements of DIN 18799
- Resistant to corrosion in neutral and slightly acidic environments
- Sturdy, easy-grip rail profiles
- Extendable using ladder connectors
- Easy to install
- Straight mounting surface required
- Fall arresting system / safety cage required: for fixed ladders on buildings and on machinery from a climbing height of 3000 mm



Scope of delivery:

Ladder sections, ladder connectors, ladder caps, wall brackets 185 mm,



exit rail (AHB-K), exit extension, safety cage rail, rear safety cage vertical bars, bar connectors, caps, max. length for shipment 4200 mm, multi-section over 4200 mm



- Rungs: perforated U-profile 30x30mm
- Non-slip rungs with perforated U-profile design

Specifications

Ladder external width in mm	490
Rung spacing 280mm	✓
Material	Steel 1.0037 / ASTM A36, galvanised
Length in m	3,08
safety cage basket Length in m	1,96
Number of rungs	11
Weight (KG)	58,0
Rail dimension	Square profile 40x20mm
Rung dimension	perforated U-profile design 30 x 30 mm
Length in m Number of rungs	3,08 m 11 Rungs
Width in mm	450

