



Harness

9698471

GTIN: 4007126027641

A suitable safety harness in a fall arrest system must be used for all work in areas at risk of falling. When selecting the right safety harness it must already be decided whether this should only serve as a fall protection, whether a combination harness with an integrated holding harness according to EN 358 or a seat harness according to EN 813 is required. The various features of the abutment possibilities (eyelets) on a safety harness are decisive. Drip eye: suitable to absorb dynamic fall stress (free fall) as well as for holding purposes. Rigging protection eyelets: fall arrester, but only to be used in conjunction with stationary climbing devices.

Version

IK G2 BWR

Applications:

- Catch
 - Seiling
 - Hold
 - Climb
 - Rescue
-
- Full body and support harness with 2 D-rings and quick locks
 - Tested to EN 361:2002, EN 358:2000 standards
 - 1 suspension and catch loop
 - 1 retaining eyelet on the back (shoulder area)
 - 1 retaining eyelet in chest area (fall arrest eyelet)
 - Integrated backrest with 2 retaining eyelets for workplace positioning
 - 4 eyelets for tool bags

PRODUCT SPECIFICATION SHEET

- Easily fits all sizes thanks to individually adjustable leg and shoulder straps
- Easy to put on and off thanks to quick locks, encourages workers to put the harness on
- Nominal load: 136 kg

operation area:

- Work in stationary fall arrest rails or fall arrester rope systems
- Scaffold construction
- Industrial use
- Work in underground structures

Specifications

Rescue loop	✓
Quick release	✓
Version	IK G2 BWR