



## HAILO G60

The aluminium multipurpose scaffold with "Fast & Lock" closure for fast and easy assembly.





### THE KEY FEATURES



- Scaffold and ladder in one
- Easy to handle and fitted with "Fast & Lock" closure for fast, easy assembly
- Multipurpose: for use as a lean-to ladder and double ladder, as a small scaffolding unit for indoors and outdoors or as a platform for working
- Step adjustment option
- 2 ladder sections of 12 rungs (27 × 27 mm) with safety joints for locking/releasing the ladder sections
- Working platform with access hatch (61 × 46 cm)
- 2 crosspieces incl. 2 transport castors
- 4 guard rails and 4 aluminium diagonal struts

### OTHER PRODUCT ADVANTAGES






- Platform dimensions: 136 × 50 cm
- Upright dimensions: 60 × 22 mm
- Rung spacing: 260 mm
- Maximum load capacity 150 kg/m<sup>2</sup>







## SPECIFICATIONS

Level of equipment		3
Can be used as lean-to ladder or free-standing ladder		✓
Can be used in a free-standing position		✓
Can be used as lean-to ladder		✓
Working platform		✓
Step adjustment		✓
Ladder sections can also be used on their own		✓
Movable		✓
Platform height		233 cm
Max. working height		433 cm
Step adjustment max.		24 cm - 28 cm
Dimensions required for setting up (WxD)		170 x 120 cm
Dimensions of packaging (HxWxD)		A = 166 cm, B = 60 cm, C = 35 cm
Weight		31,0 kg
Load capacity		150 kg/m <sup>2</sup>