# Shaft cover HS8-R burglar proof (RC3 - DIN 1627)

## 9541027

GTIN: 4007126266217

Shaft cover flush to the ground, suitable for cars (EN 124 class B) or trucks (EN 124 class D), approved for flowing urban traffic. Safe operation with gas pressured springs as opening aid and self-engaging cover. Lid with integrated seal. Locked by closure with brass nut for male triangular wrench. Incl. the necessary number of anti-burglary lock inserts (burglar resistance class RC3 according to DIN 1627) with drill-proof and pull-proof security lock. Deeper locking covered by three-sided brass bolt. Other sizes, versions and materials on request.

Width in mm
800 mm

Load class
D 400kN - EN124

- burglar proof - tested by IFT Rosenheim

- circular design
- surface water proof
- safe to drive on
- odour proof
- for installation at ground level
- stainless steel 1.4301/ASTM 304
- incl. the necessary number of anti-burglary lock inserts (burglar resistance class RC3 according to DIN 1627) with drill-proof and pull-proof security lock


Copyright © 2026 Hailo. Alle Rechte vorbehalten.

options on request:




- material Steel galvanised 1.4571 / ASTM 316
- Tiemergency unlocking to allow the cover to be opened from below
- backpressure/flood proof 0.2 bar
- electric or hydraulic opening



## Specifications

| | |
|---|---|
| Burglar resistance | RC3 according to DIN 1627 |
| Material | Stainless steel 1.4301 / AISI 304 |
| Thightness | surface water proof |
| flush with ground | ✔ |
| circular | ✔ |
| suitable for moving traffic | ✔ |
| Load class | D 400kN - EN124 |
| Width in mm | 800 mm |





Copyright © 2026 Hailo. Alle Rechte vorbehalten.