




HAILO S98 PROFILOT

3-section aluminium combination ladder with LOT System for level adjustment.


THE KEY FEATURES

- LOT System: compensates for uneven ground up to 15 cm, adjusted by pedal
- Versatile to use as a lean-to, extending or trestle ladder
- 2 attachable full surface-contact feet and 2 large stable claw feet



OTHER PRODUCT ADVANTAGES



- Locking hook with transport locking mechanism
- Length and cross-profiled rungs
- Non-removable third ladder section
- Max. load capacity 150kg



SPECIFICATIONS

Level of equipment		5
LOT System		✓
Locking hook with transport locking mechanism		✓
Can be used as lean-to ladder or free-standing ladder		✓
Can be used in a free-standing position		✓
Can be used as lean-to ladder		✓
Number of steps		3 x 12
Width/depth required for setting up lean-to ladder		A = 150 cm, B = 216 cm
Width/depth required for setting up extending ladder		A = 150 cm, B = 221 cm
Height of lean-to ladder		807 cm
Height of extending ladder		555 cm
Max. working height		901 cm



Max. working height of trestle ladder		438 cm
Max. working height of lean-to ladder		901 cm
Max. working height of extending ladder		598 cm
Dimensions of packaging (HxWxD)		A = 360 cm, B = 48 cm, C = 21 cm
Weight		29,2 kg
Load capacity		150 kg