



## Bridging steps, fixed, 60°

**6067421**

GTIN: 4007126262585

HAILO offers fixed bridging steps for the safe crossing of obstacles. Whether machine systems, storage facilities, packaging or production lines - wherever people need to safely cross an obstacle, the modular bridging steps are used in accordance with the specifications of the European standard EN ISO 14122 and EN 131-7. Depending on requirements, different angles of inclination of the steps and different tread widths of the steps can be selected. All variants are ergonomically optimized and thus enable the user to ascend and descend safely and comfortably. They are supplied in pre-assembled modules, which reduces the time and effort required for final assembly. Detailed assembly instructions are included in the delivery. Special designs are of course available on request.

Step width (mm)  
600

Number of steps  
3

- Modular system
- Platform length 900 mm
- Incl. handrail and railing on one side (optional handrail on both sides at extra charge)
- Non-slip ribbed steps & platform
- Quick assembly thanks to pre-assembled components

Options on request:





- 75° variant for confined spaces
- Mobile version with central brake function
- R13 slip resistance for steps and platform
- Ballast weights for penetration-free installation on roofs
- Outdoor version (all screw connections made of stainless steel)

Specifications

Material	Aluminium AlMg3 / AlMgSi 0,5
Inclination	60°
Step depth (mm)	225
Handrail (in mm)	Ø 40
Platform length (mm)	Standard 900
Railing one-sided	✓
Step width (mm)	600
Number of steps	3
Clearance height (mm)	700
Clear depth platform (mm)	590
Total height (mm)	1840
Total depth (mm)	1885
Weight (KG)	43
Product code	ÜS-S-600-60-3-60-3-P2-G E-GE-I

