



Platform stairs, wall-mounted,  
inclination 45°

**6068701**

GTIN: 4007126264046

HAILO offers stationary, modular platform stairs that meet the requirements of the European standard EN ISO 14122 for safe access to higher workstations, machinery or storage facilities. Depending on requirements, different angles of inclination of the stairway ascent and different tread widths can be selected. All variants are ergonomically optimized and thus enable the user to ascend and descend safely and comfortably. They are supplied in pre-assembled modules, which reduces the time and effort required for final assembly. Detailed assembly instructions are included in the delivery. Special designs are of course available on request.


Step width (mm)  
600

Number of steps  
3

- Modular system
- Platform length 675 mm
- Incl. handrail and railing on one side (optional handrail on both sides at extra charge)
- Non-slip ribbed steps & platform
- Quick assembly thanks to pre-assembled components

Options on request:

- 75° variant for confined spaces
- R13 slip resistance for steps and landing





- Version for outdoor use
- Execution as elevated version



Specifications

Material	Aluminium AlMg3 / AlMgSi 0,5
Inclination	45°
Step depth (mm)	225
Handrail (in mm)	Ø 40
Platform length (mm)	Standard 675
Railing one-sided	✓
Step width (mm)	600
Number of steps	3
Clearance height (mm)	610
Clear depth platform (mm)	510
Total height (mm)	1750
Total depth (mm)	1260
Weight (KG)	28
Product code	PT-W-600-45-3-P2-GE-I