Platform stairs, inclination 45°

6073831

GTIN: 4007126263476

With its mobile, modular ALU platform steps, HAILO offers a mobile version for use on shelving, storage facilities or assembly work in accordance with the European standard EN ISO 14122.

Step width (mm)
800

Number of steps
8





A robust chassis combined with high-quality swivel castors Ø160mm and the HAILO central braking system allow you to move quickly and stand securely.
Depending on your requirements, you can select different angles of inclination for the stairway and different tread widths for the steps. All variants are ergonomically optimized and thus enable the user to ascend and descend safely and comfortably.
They are supplied in pre-assembled modules, which reduces the time and effort required for final assembly. Detailed assembly instructions are included in the delivery.
Special designs are of course available on request.

- Robust chassis with Ø160mm castors
- Central brake function
- Modular construction system
- Platform length 675mm
- With handrail on both sides and 3-sided guardrail as standard
- Non-slip ribbed steps & platform
- Quick assembly thanks to pre-assembled components

Options on request:

- 75° variant for confined spaces

Copyright © 2026 Hailo. Alle Rechte vorbehalten.

PRODUCT SPECIFICATION SHEET

- R13 slip resistance for steps and landing
- Version for outdoor use

Specifications

Material	Aluminium AlMg3 / AlMgSi 0,5
Inclination	45°
Step depth (mm)	225
Handrail (in mm)	Ø 40
Platform length (mm)	Standard 675
All-round railing	✔
BG Bau subsidy possible	✔
Step width (mm)	800
Number of steps	8
Vertical height (mm)	1770
Platform depth (mm)	675
Total height (mm)	2870
Total depth (mm)	2370
Total width (mm)	1310
Weight (KG)	119
Product code	PT-F-800-45-8-P2-GB-I

Copyright © 2026 Hailo. Alle Rechte vorbehalten.